FILAACTIVE1 **ACTIVE MOULD REMOVER**





- CERAMIC
- PORCELAIN
- NATURAL STONE
- GROUT JOINTS
- CONCRETE
- TERRACOTTA
- WALL PAINT



WHAT'S IT FOR

■ Rapidly removes mould and sanitises stone, plaster, cement, grouting, ceramic, glass and marmorino plaster surfaces.

ADVANTAGES

- Easy-to-use, ergonomic container with spray applicator.
- Ideal viscosity: can be easily applied to walls.
- Acts rapidly and effectively within a few minutes.
- Effectively removes mould from grouting.

HOW TO USE

Ready to use: no dilution required

Application:

Spray FILAACTIVE1 directly onto the surface to be cleaned, from a distance of about 15-20 cm, while keeping the bottle upright. Leave to act for approximately 15 minutes. Soak up any excess product with a damp cloth to prevent dripping. Repeat if necessary, then wipe the surface clean with a damp sponge.

Packaging

500 ml bottles with spray nozzle (trigger): 12-piece cartons.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
 Do not use in conjunction with acids. It may produce hazardous gas (chlorine).
- Ventilate the room during and after application.
- Do not remove dry mould in order to prevent dispersion of the spores.

TEMPERATURES

Storage temperature: from 5° to 30° C.
The product should be applied to materials with temperature between 5° and 30° C.

Non-ionic surfactants < 5%, chlorine bleaches 5-15%. Contains: 5% active chlorine solution.

UK MARKET ONLY: HSE NO 9667

COVERAGE

With 500 ml:

5-10 m² the coverage varies depending on the material's absorption capacity

The coverage is purely indicative

Caution:

do not spray on plants, fabrics and metals. Should this occur, wash immediately with water. Do not use on new polished stone. Caution: before using on coloured plaster, first try on a small section to avoid possible colour alterations.

LABELLING Warning: Danger

Hazard indication:
May be corrosive to metals. Causes severe skin burns and eye damage. Very toxic to aquatic life.
Toxic to aquatic life with long lasting effects. Contact with acids liberates toxic gas. Warning! Do not use together with other products. May release dangerous gases

Caution recommendations: If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep only in original container. Do not breathe dust / fume / gas / mist / vapours / spray. Wear protective gloves / clothing and eye / face protection. Absorb spillage to prevent material damage. Dispose of contents / container in accordance with official regulations Contains: SODIUM HYDROXIDE, SODIUM HYPOCHLORITE, N,N-Dimethyltetradecylamine N-oxide

TECHNICAL FEATURES

Appearance: transparent viscous liquid Odour: typical pungent

Density: 1.111 kg/l **pH:** 13.5

This information is the result of our most up-todate technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.

REV. 00 - 21/01/2016

